

# PrOlix® Tech Tips: Cleaning Suggestions

---

## Tools needed:

Manufacturer's original owners manual (if available);  
**PrOlix® #1 Total Gun Care Product (TGCP) and PrOlix® XTRA-T™ LUBE;**  
J-B's Bore Cleaner(s) (**PrO item #184**);  
Cleaning Kit with proper size Rod (SS-Stainless Steel) and tips (Brass or SS) for Bore size;\*  
Bore Light;  
Guide, Cleaning Rod or Muzzle;  
Shop towel or Gunsmiths bench/Cleaning Pad (**PrO item(s) #177Small & #177Large**);  
Patches (GI style for general wiping; Fiber material for cleaning the bore, as **PrO item #182**);  
Parts Cleaning Brush, (1) M-16 style (**PrO item #179**); (2) SD PipeC/Brush (**PrO item #178**);  
Brass(Bronze) or Steel Wool '0000' or finer; get one of each with (**PrO item #179W**);  
Short wooden dowel (sharpen like a pencil);  
Cleaning pan, various sizes for whatever your needs are to soak parts; (**See website for ideas!**)  
(\***PrOlix®** has a SS Universal Field Kit for .22-10GA **PrO item #181**)

## Cleaning:

First, place firearm on a shop towel or gunsmiths pad and take down according to the manufacturer's instructions or to a point that you are capable. One of the advantages of using our product, **PrOlix® TGCP**, is that you don't have to take the firearm apart at all; it will get down into the smallest of spaces, Clean and Lubricate all by its self! That is with your great help! Next, lightly, tap the short wooden dowel into the muzzle and making sure you have it supported, stand the firearm upright on this dowel (in a can or cleaning pan) and pour the bore full of the **PrOlix® TGCP**, close the bolt (or use foil to cap the pistol barrel). Let set for fifteen minutes or days if necessary, while you clean the other parts. Make sure the **PrOlix® TGCP** doesn't leak out, it will leak until the dowel swells and seals! Then remove the wooden dowel, letting the cleaner run into the can or pan and take the cleaning rod and proper jag-tip or brush, soak it good, and run it thru the bore until clean. Always, do the cleaning from the breach end and use a Rod Guide in place of the bolt or a muzzle guide if you can't clean from the breach! If it is fouled or in real bad shape, generally, you can take J-B's Bore Cleaner thinned out with **PrOlix® TGCP** on a worn brush wrapped with a Fiber type cleaning patch to clear the bore and then go back to the wooden dowel and let the bore soak again! Once clean (check with bore light) and clear, you are ready to clean the outside and store, display, or ready for a trip to the range! The outside should be wiped or sprayed (liberally) with **PrOlix® TGCP**, let set awhile then soak again and if there is build up or rust spots use the '0000' Brass/Steel Wool and the Cleaning Brushes, as the other **PrOlix® TGCP** info notes, it won't harm wood! Clean to your satisfaction with well saturated Patches or a Shop rag! If you soak the parts using **PrOlix® TGCP**, it can be poured back into the original container, using a funnel packed with Cheese-Cloth (**PrO item #180**), and used over and over again until there is nothing remaining or it gets thick and un-usable! Even, when it looks dirty, it still works for the first step cleaning, BUT remember to use clean Patches/Rags soaked with **PrOlix® TGCP** for the final wipe down! You are now ready to store/display or if you go to the range, be sure and take the **PrOlix® TGCP** and treat the bore while hot! This will coat the bore, deeply, and help to cut-down any fouling and make each cleaning get easier and easier! Remember, **PrOlix® TGCP** WILL NOT refinish or repair any damaged wood or metal!!! **PrOlix® TGCP** will clean, protect, and enhance ANY FINISH it's applied to and WILL prevent rust from returning! So, go ahead now...and let **PrOlix® TGCP** amaze you, too! The Best test is yours!! So, if you need additional Help or Have a question, please give us a CALL! PJL©0409